

Schuller Eh'klar GmbH
AUSTRIA
Im Astenfeld 6
A – 4490 St. Florian
Tel.(0043) 07224/68 200
Fax(0043) 07224/68 282
E-Mail: office@schuller.eu
www.schuller.eu

Schuller
Eh'klar

St. Florian, 02.04.2013

UV-FOLI TAPE

(Articlenumbers: 46402, 46403, 46405, 46405, 46413)

Description:

Self-adhesive protective film for glass surfaces.

- The film is not harmful and can be completely recycled
- The film is not suitable for the protection of metals and mirrored glass surfaces
- Applications include glass, aluminium, PVC and stainless steel, wood, ceramic

Technical data:

material	LDPE-Folie
adhesive	Acrylat
strentgh	50my (±10%)
density	0,922
weight	46g/m2 (±10%)
adhesion strength	>80 cN/cm (AFERA 4001; Glas)
elongation (lengthwise)	>200%
elongation (crosswise)	>400%
application temperatur	-5°C - +35°C (dry surface)

Application:

- Don't remove the film with sudden movements from the glass surfaces
- The film must be applied to dry and clean surface. The application must be made without fat, air bubbles or excessive stretching of the film
- The film must be removed within 4 weeks
- Test adhesion necessary

Storage:

Storage at room temperature (between 10 ° C and +30 ° C at a relative humidity of 50%). Keep away from direct sunlight and other heat sources. In compliance with the storage conditions, the film can be stored for 6 to 12 months.