

Schuller Eh'klar GmbH
AUSTRIA
Im Astenfeld 6
A – 4490 St. Florian
Tel.(0043) 07224/68 200
Fax(0043) 07224/68 282
E-Mail: office@schuller.eu
www.schuller.eu

Schuller
Eh'klar

St. Florian, 29.10.2013

MASKING TAPE “4500”

(Articlenumbers: 45003, 45005, 45006, 45007, 45009)

Description:

Impregnated water repellent Krepptape with excellent adhesive properties (with high adhesive strength) on most surfaces. The masking tape is characterized by a very high temperature resistance and is therefore ideally suitable for all professional painting and decorating work. The tape is compatible for all common paints and coatings, can be torn off by hand and is removeable with no residues.

Datas:

backing	impregnated Krepp paper	
adhesive	natural rubber	
total thickness	145my ($\pm 10\%$)	
adhesion on steel	>2,8 N/cm (>2,2 N/cm)	
tensile strength	50 N/cm (25-65 N/cm)	
elongation to break	8% (6-12%)	
steel ball roll test	<1 cm (<3cm)	
temperature resistant	+120°C	
UV-resistant	72 hours (Ultra Vitalux Osram)	

Application:

The surface must be free of grease and dust. According to the painting or repainting, the tape should be removed as soon as possible. This will prevent any glue residues. This tape is UV resistant (Ultra Vitalux Osram). Before you do the really work, you have to do a testing before.

Storage:

Storage at room temperature (23°C / 50% relative humidity). Keep away from direct sunlight and other heat sources. In compliance with the storage conditions, the tape can be stored for 12 months.