



Safety Data Sheet dated 05.05.2021

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Mixture identification:

Trade name: PRISMA COLOR RAL Spray ACRYL

Trade code: 91000Series

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Spray painting decorative household, industrial and professional

### 1.3. Details of the supplier of the safety data sheet

Company:

**Schuller Eh' klar GmbH, Im Astenfeld 6, A-4490, St. Florian**

**Tel.: +43(7224) 68200; Fax: +43 (7224) 68282**

Competent person responsible for the safety data sheet:

[office@schuller.eu](mailto:office@schuller.eu)

### 1.4. Emergency telephone number:

Poison Control Center Austria: +43 (1) 406 43 43

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP):



Danger, Aerosols 1, Extremely flammable aerosol. Pressurized container: may burst if heated.



Warning, Skin Irrit. 2, Causes skin irritation.



Warning, Eye Irrit. 2, Causes serious eye irritation.



Warning, STOT SE 3, May cause drowsiness or dizziness.

Adverse physicochemical, human health and environmental effects:

No other hazards

### 2.2. Label elements

Hazard pictograms:



Danger

Hazard statements:

H222+H229 Extremely flammable aerosol. Pressurized container: may burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

Safety Data Sheet

PRISMA COLOR RAL Spray ACRYL

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P271 Use only outdoors or in a well-ventilated area.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Contains

Acetone; propan-2-one; propanone

n-butyl acetate

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards:

No other hazards










### SECTION 3: Composition/information on ingredients

3.1. Substances













N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number	Classification
>= 25% - < 30%	Acetone; Propan-2-one; propanone	Index number: 606-001-00-8 CAS: 67-64-1 EC: 200-662-2 REACH No.: 01-2119471330-49	 2.6/2 Flam. Liq. 2 H225  3.3/2 Eye Irrit. 2 H319  3.8/3 STOT SE 3 H336 EUH066
>= 15% - < 20%	propane	Index number: 601-003-00-5 CAS: 74-98-6 EC: 200-827-9 REACH No.: 01-2119486944-21	 2.2/1 Flam. Gas 1 H220  2.5/L Press Gas (Liq.) H280
>= 7% - < 10%	n-butyl acetate	Index number: 607-025-00-1 CAS: 123-86-4 EC: 204-658-1 REACH No.: 01-2119485493-29	 2.6/3 Flam. Liq. 3 H226  3.8/3 STOT SE 3 H336 EUH066
>= 7% - < 10%	butane	Index number: 601-004-00-0 CAS: 106-97-8 EC: 203-448-7	 2.2/1 Flam. Gas 1 H220  2.5/L Press Gas (Liq.) H280

Safety Data Sheet  
PRISMA COLOR RAL Spray ACRYL

		REACH No.: 01-2119474691-32	
>= 7% - < 10%	xylene	Index number: 601-004-00-0 CAS: 1330-20-7 EC: 215-535-7 REACH No.: 01-2119488216-32	 3.6/3 Flam. Liq. 3 H226  3.1/4/Dermal Acute Tox. 4 H312  3.1/4/Inhal Acute Tox. 4 H332  3.2/2 Skin Irrit. 2 H315
>= 5% - < 7%	Isobutane; 2-Methylpropane	Index number: 601-004-00-0 CAS: 75-28-5 EC: 200-857-2 REACH No.: 01-2119485395-27	 2.2/1 Flam. Gas 1 H220  2.5/L Press Gas (Liq.) H280
>= 1% - < 2.5%	2-butoxyethanol; Ethyleneglycol monobutyl ether; butyl cellosolve	Index number: 603-014-00-0 CAS: 111-76-2 EC: 203-905-0 REACH No.: 01-2119475108-36	 3.1/4/Dermal Acute Tox. 4 H312  3.1/4/Inhal Acute Tox. 4 H332  3.1/4/Oral Acute Tox. 4 H302  3.2/2 Skin Irrit. 2 H315  3.3/2 Eye Irrit. 2 H319
>= 1% - < 2.5%	Dimethyl carbonate	Index number: 607-013-00-6 CAS: 616-38-6 EC: 210-478-4 REACH No.: 01-2119548399-23	 2.6/2 Flam. Liq. 2 H225

#### SECTION 4: First aid measures

##### 4.1. Description of first aid measures

###### In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

###### In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

###### In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

###### In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

##### 4.2. Most important symptoms and effects, both acute and delayed

None

##### 4.3. Indication of any immediate medical attention and special treatment needed

Safety Data Sheet

PRISMA COLOR RAL Spray ACRYL

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

---

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media:

CO2 or Dry chemical fire extinguisher.

Extinguishing media which must not be used for safety reasons:

None in particular.

### 5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

### 5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

---

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

See protective measures under point 7 and 8.

### 6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

### 6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

### 6.4. Reference to other sections

See also section 8 and 13

---

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

### 7.2. Conditions for safe storage, including any incompatibilities

Store at below 20 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.



Schuller Eh'klar GmbH EUROPE  
Im Astenfeld 6  
A-4490 St. Florian  
Tel.: +43 (7224) 68 200  
Fax.: +43 (7224) 68 282  
Email: [office@schuller.eu](mailto:office@schuller.eu)

Safety Data Sheet

PRISMA COLOR RAL Spray ACRYL

### 7.3. Specific end use(s)

None in particular

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

acetone; propan-2-one; propanone - CAS: 67-64-1

EU - TWA(8h): 1210 mg/m<sup>3</sup>, 500 ppm

ACGIH - TWA(8h): 250 ppm - STEL: 500 ppm - Notes: A4, BEI - URT and eye irr, CNS impair

propane - CAS: 74-98-6

ACGIH - Notes: (D, EX) - Asphyxia

VLE short - 1000 ppm

n-butyl acetate - CAS: 123-86-4

ACGIH - TWA(8h): 50 ppm - STEL: 150 ppm - Notes: Eye and URT irr

EU - TWA(8h): 241 mg/m<sup>3</sup>, 50 ppm - STEL: 723 mg/m<sup>3</sup>, 150 ppm

butane - CAS: 106-97-8

ACGIH - STEL: 1000 ppm - Notes: (EX) - CNS impair

xylene - CAS: 1330-20-7

EU - TWA(8h): 221 mg/m<sup>3</sup>, 50 ppm - STEL: 442 mg/m<sup>3</sup>, 100 ppm - Notes: Skin

ACGIH - TWA(8h): 100 ppm - STEL: 150 ppm - Notes: A4, BEI - URT and eye irr, CNS impair

Isobutane 2- Methylpropane - CAS: 75-28-5

ACGIH - STEL: 1000 ppm - Notes: (EX) - CNS impair

VLE short - 1000 ppm

2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve - CAS: 111-76-2

EU - TWA(8h): 98 mg/m<sup>3</sup>, 20 ppm - STEL: 246 mg/m<sup>3</sup>, 50 ppm - Notes: Skin

ACGIH - TWA(8h): 20 ppm - Notes: A3, BEI - Eye and URT irr

DNEL Exposure Limit Values

N.A.

PNEC Exposure Limit Values

N.A.

### 8.2. Exposure controls

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

No special precaution must be adopted for normal use.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use adequate protective respiratory equipment.

Thermal Hazards:

None

Environmental exposure controls:

None

Appropriate engineering controls:

None

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Properties	Value	Method	Note
Appearance and colour	Liquid aspect (under pressure),		



Schuller Eh'klar GmbH EUROPE  
Im Astenfeld 6  
A-4490 St. Florian  
Tel.: +43 (7224) 68 200  
Fax.: +43 (7224) 68 282  
Email: [office@schuller.eu](mailto:office@schuller.eu)

Safety Data Sheet  
PRISMA COLOR RAL Spray ACRYL

	various colours.		
Odour:	Characteristic of solvent		
Odour threshold:	Non Dispobibile		
pH:	8		
Melting point / freezing point:	Non Disponibile		
Initial boiling point and boiling range:	Non Disponibile		
Flash point:	Inf. 0 ° C		
Evaporation rate:	Non Disponibile		
Solid/gas flammability:	Extremely flammable		
Upper/lower flammability or explosive limits:	Inf. 0°C		
Vapour pressure:	at 20°C - 4,0 bar ; at 50°C - 8,0 bar		
Vapour density:	N.A.		
Relative density:	0,75 - 0,80 g/ml		
Solubility in water:	NO		
Solubility in oil:	YES		
Partition coefficient (n-octanol/water):	Non Disponibile		
Auto-ignition temperature:	Non Auto-ignitionable		
Decomposition temperature:	Non Disponibile		
Viscosity:	10-12		
Explosive properties:	NO		
Oxidizing properties:	NO		

9.2. Other information

Properties	Value	Method:	Notes:
Miscibility:	N.A.	--	--
Fat Solubility:	N.A.	--	--
Conductivity:	N.A.	--	--
Substance Groups relevant properties	N.A.	--	--

**SECTION 10: Stability and reactivity**

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None



Schuller Eh'klar GmbH EUROPE  
Im Astenfeld 6  
A-4490 St. Florian  
Tel.: +43 (7224) 68 200  
Fax.: +43 (7224) 68 282  
Email: [office@schuller.eu](mailto:office@schuller.eu)

Safety Data Sheet

PRISMA COLOR RAL Spray ACRYL

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

10.6. Hazardous decomposition products

None.

---

**SECTION 11: Toxicological information**

11.1. Information on toxicological effects

Toxicological information of the product:

PRISMA COLOR

a) skin corrosion/irritation: H315 Causes skin irritation.

b) serious eye damage/irritation: H319 Causes serious eye irritation.

c) STOT-single exposure: H336 May cause drowsiness or dizziness.

Toxicological information of the main substances found in the product:

acetone; propan-2-one; propanone - CAS: 67-64-1

LD50 (RABBIT) ORAL: 5300 MG/KG

xylene - CAS: 1330-20-7

LD50 (RAT) ORAL: 5000 MG/KG

2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve - CAS: 111-76-2

LD50 (RABBIT) ORAL: 320 MG/KG

If not differently specified, the information required in Regulation (EU)2015/830 listed below must be considered as N.A.:

a) acute toxicity

b) respiratory or skin sensitisation;

c) germ cell mutagenicity;

d) carcinogenicity;

e) reproductive toxicity;

f) STOT-repeated exposure;

g) aspiration hazard.

---

**SECTION 12: Ecological information**

12.1. Toxicity

Adopt good working practices, so that the product PRISMA COLOR is not released into the environment.

According to the data available, the product meets no classification criteria.

12.2. Persistence and degradability

None

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects

None

---

**SECTION 13: Disposal considerations**

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

---

## SECTION 14: Transport information

### 14.1. UN number

Not classified as dangerous in the meaning of transport regulations.

ADR-UN number: 1950

IATA-Un number: 1950

IMDG-Un number: 1950

### 14.2. UN proper shipping name

ADR-Shipping Name: Aerosol

IATA-Technical name: Aerosol

IMDG-Technical name: Aerosol

N.A.

### 14.3. Transport hazard class(es)

ADR-Class: 2 5F

ADR-Label: 2

ADR - Hazard identification number: -

IATA-Class: 2.1

IATA-Label: 2.1

IMDG-Class: 2

N.A.

### 14.4. Packing group

ADR-Packing Group: -

IATA-Packing group: -

IMDG-Packing group: -

N.A.

### 14.5. Environmental hazards

Marine pollutant: Marine pollutant

N.A.

### 14.6. Special precautions for user

IATA-Passenger Aircraft: ---

IATA-Cargo Aircraft: 203

IMDG-Technical name: Aerosol

IMDG-Page: F-D, S-U

N.A.

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

N.A.

---

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) 2015/830

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)



Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3

Restriction 40

Restrictions related to the substances contained:

N.A.

Volatile Organic compounds - VOCs = 622.50 g/l

Volatile CMR substances = 0.00 %

Halogenated VOCs which are assigned the risk phrase R40 = 0.00 %

Organic Carbon - C = 0.01

Where applicable, refer to the following regulatory provisions :

Directive 2012/18/EU (Seveso III)

Regulation (EC) nr 648/2004 (detergents).

Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

Product belongs to category: P3a

#### 15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

### SECTION 16: Other information

Text of phrases referred to under heading 3:

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H226 Flammable liquid and vapour.

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H302 Harmful if swallowed.

Hazard class and hazard category	Code	Description
Flam. Gas 1	2.2/1	Flammable gas, Category 1
Aerosols 1	2.3/1	Aerosol, Category 1
Press Gas (Liq.)	2.5/L	Gases under pressure (Liquefied gas)
Flam. Liq. 2	2.6/2	Flammable liquid, Category 2
Flam. Liq. 3	2.6/3	Flammable liquid, Category 3
Acute Tox. 4	3.1/4/Dermal	Acute toxicity (dermal), Category 4
Acute Tox. 4	3.1/4/Inhal	Acute toxicity (inhalation), Category 4
Acute Tox. 4	3.1/4/Oral	Acute toxicity (oral), Category 4
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3

Paragraphs modified from the previous revision:

SECTION 2: Hazards identification  
SECTION 3: Composition/information on ingredients  
SECTION 8: Exposure controls/personal protection  
SECTION 11: Toxicological information  
SECTION 12: Ecological information  
SECTION 16: Other information

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Aerosols 1, H222+H229	On basis of test data
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
STOT SE 3, H336	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,  
Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van  
Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date.  
It refers solely to the product indicated and constitutes no guarantee of particular quality.  
It is the duty of the user to ensure that this information is appropriate and complete with respect to  
the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE:	Acute Toxicity Estimate
ATEmix:	Acute Toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
PNEC:	Predicted No Effect Concentration.



Schuller Eh'klar GmbH EUROPE  
Im Astenfeld 6  
A-4490 St. Florian  
Tel.: +43 (7224) 68 200  
Fax.: +43 (7224) 68 282  
Email: [office@schuller.eu](mailto:office@schuller.eu)

Safety Data Sheet

PRISMA COLOR RAL Spray ACRYL

RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
WGK:	German Water Hazard Class.