



Product data sheet PVC MASK Q

Article nr. **45446,45449,45456,45457,45459**

Short description:

Protection adhesive tapes made of robust and strong carrier but still easy to tear off. Very high adhesion, stick well also on rough surfaces. UV-resistant for plastering-, stucco-, and protection works indoor and outdoor

Application:

The surface to be masked must be free of grease, dust and dry. . It is mainly used for wood (painted, primed), aluminum and glass.

Increased caution is required for soft and porous substrates (softwood, plaster, paint), weathered PVC substrates and surfaces containing plasticizers. Therefore, it is essential to carry out a relevant test bonding before the actual work. The plasticizer of the PVC can damage water-based paints and stains.

Product data sheet PVC MASK Q

Article nr 45446,45449,45456,45457,45459

Productdata adhesive tape:

Carrier material	Soft PVC	
Adhesive	rubber	
Carrier thickness (mm)	0,12 mm	
Total thickness	0,155 mm (+/- 10%)	ASTM D 1000
Adhesion to steel (N/mm)	2,9N/25mm	ASTM D 1000
Tensile strenght (N/mm)	29,5N/25mm	ASTM D 1000
Elongation at break (%)	90%	ASTM D 1000
Temperature resistance (°C)	until +60°C	
UV-resistance	Outdoor until 2 weeks max.	



Conditions:

Store in a cool and dry place, away from sunlight and direct heat sources (15-23°C / 50% relative humidity). As far as the storage conditions are respected, the product is guaranteed 12 months.



If you need further informations, we are at your disposal.