



Product data sheet **WHITE Mask**

Article number: 45329, 45326

Characteristics:

This protection tape consists of a flat PE fabric backing coated with a special acrylate adhesive.

- Very good adhesive properties on different surfaces
- Can be removed without residue and can be repositioned several times
- Strong, non-stretchable carrier and therefore dimensionally stable for perfect straight colouredges lines
- easy tearable with hands, clean and straight cutting edge.

Applications:

- Indoor and outdoor – surface covering and protection (e.g., baseboards, door and window frames, window sills, walls, and floors, etc.) during painting and plastering work.
- Removable without residue from most surfaces for up to 30 days, indoors and outdoors.
- Special care is required on soft and porous surfaces (softwood, stone, wallpaper, paint), weathered PVC surfaces, and surfaces containing plasticizers.
- Always perform a test application before starting actual work!

Product data sheet
WHITE Mask

Article number: 45329, 45326

Product data:	
Backing	Polyethylene fabric
Adhesive	Acrylate Adhesive
Color	white
Adhesive tape width	50 mm, 30mm
Tape length	25 m
Heat resistance (C°)	80°C for an hour
Adhesive to steel (N/cm)	3,0-4,5
Tensile strength (N/cm)	≥ 70
Elongation (%)	30-60
Total thickness (µm)	170 ±10
UV-resistance	Indoor and outdoor up to 30 days



Conditions:

Store in a cool and dry place, away from sunlight and direct heat sources (15-23°C / 50% relative humidity). As far as the storage conditions are respected, the product is guaranteed 12 months.



If you need further informations, we are at your disposal.