

Schuller Eh'klar GmbH  
 AUSTRIA  
 Im Astenfeld 6  
 A – 4490 St. Florian  
 Tel.(0043) 07224/68 200  
 Fax(0043) 07224/68 282  
 E-Mail: office@schuller.eu  
 www.schuller.eu



St. Florian, 04.05.2026

# DUCT TAPE “X-Way”

(Articlenumber: 45778, 45779, 45797, 45761,45763)

## Description:

Duct tape for the construction sector. A standard tape with a soft, synthetic rubber adhesive and good resistance against aging and temperature. As the backing serves a strong, weatherproof and waterproof coated, handtearable, polyester fabric. This tape is characterized by a very strong initial tack, good adhesion and excellent adhesion in the freezing point

## Product datas:

Backing	LDPE-film + Polyester fabric
Adhesive	Synthetic rubber (solventfree)
Mesh	32
Total thickness	0,165 mm
Adhesion to steel	20 N/25mm
Tensile strenght	75 N/25mm
Rolling ball tack	<3 cm
Application temperature	-10°C - +75°C

## Application:

This tape sticks perfectly on smooth and rough surfaces such as stone, concrete, wood and plastic and is for professional work indoors and outdoors.

## Conditions:

Store in a cool and dry place, away from sunlight and direct heat. As far as the storage conditions are respected, the product is garanteed 12 months.