



DRYWALLTAPE

Item-Nr. 45540, 45544 and 45549

Description:

This self-adhesive, tear-resistant fiberglass tape is used to fill the joints between drywall panels and to bridge holes and cracks.

Storage:

Store in a dry place at room temperature between -10°C and 50°C. Keep away from direct sunlight and other sources of heat.

Application:

Before using the fiberglass tape, the surface must be free of dust and grease. Then apply the joint tape and press it down gently. Now apply a layer of joint compound over the joint tape.

DRYWALLTAPE

Item-Nr. 45540, 45544 and 45549

Technical specifications			
Backing material	fiberglass fabric tape		
Fabric weight, including adhesive	64,5 g/m ² ± 3,5 g/m ²		
Finishing Agents and Adhesives	41-47 % of the weight		
Fabric density	Per 10 cm	35,4 lengthwise	35,4 crosswise
Total thickness	0,26 mm		
Tensile strength	N/2,54 cm	260	483
Tensile strength	30 kg / 25 x 25mm		

Art. Nr.	EAN-Code	Article text	PE 1	PE 2
45540	9002588455402	Drywall Tape Pro 48mmx20m self-adhesive fiber tape	48	1440
45544	9002588455440	Drywall Tape Pro 48mmx90m self-adhesive fiber tape	24	480
45549	9002588455495	Drywall Tape Pro 144mmx90m self-adhesive fiber tape	6	180



If you need any further informations, we are at your disposal.