



Datasheet **SUNCORE ECO**

Item No. **45526, 45527, 45529**

Product Description:

The SunCore Eco with 30 days UV resistance is the ideal solution for those looking for reliable and at the same time economical masking. It convinces with clean paint edges, good adhesion and residue-free removal, ideal for simple painting, renovation and DIY work indoors and outdoors.

The perfect entry-level quality for daily use when functionality and price are the focus.

Applications:

- Indoor and outdoor surface coverage, surface protection (such as skirting boards, door and window frames, window sills, walls and floors, etc.) in painting and plastering.
- Can be removed without leaving any residue for up to 60 days indoors and 30 days outdoors
- Increased caution is required with soft and porous substrates (softwood, wallpaper, paint), weathered PVC substrates and surfaces containing plasticizers.
- Always perform a test application before starting actual work!!

Datasheet **SUNCORE Eco**

Item No. 45526, 45527, 45529

Product data:

Carrier material	Washi Paper
Glue	Acrylate Adhesive
Color	Apple green
Adhesive Tape Width	30/36/48 mm
Tape length	50 m
Temperature resistance	80°C for a short time for 30 minutes
Adhesive strength (hour/0.5Kg)	≥8
Tensile strength (N/10 mm)	32-42
Elongation (%/10 mm)	5-10
Total thickness µm	100 ±10
UV resistance	Indoors up to 60 days
	Outdoor up to 30 days

Storage:

Store in a clean, dry, and shaded place.

A temperature of 20°C and a relative humidity of 65% are recommended.



If you need further information's, we are at your disposal.